

The Quality Connection



Manufacturing for Special Cleanliness Grades

Our experienced Engineering team designs cables for varying grades of cleanliness based on our customers purity requirements.

> Single wires

> Power cables

> Data cables

> Prototyping

We connect your Clean Room

2

LEONI is your reliable partner in the development and manufacturing of tailor-made cables, and your knowledge center for sophisticated connection technology for clean room applications.



Numerous industry branches and application types

increasingly require clean and largely particle-free

LEONI delivers clean room cable for manufacturing

Cleanliness Class 1. Various solutions also fulfils all

areas and fulfils all requirements up to Air

requirements which are needed in ultra high

components and systems.

vacuum environment.

LEONI

Applications >

- Semiconductor industry
- Display industry
- Optical industry
- Metrology
- Aerospace technology
- Micro- and nanostructure
- technology
- Packaging technology Drag chain applications
- Drag less applications

Due to our stict quality management all clean room cables can be tested as follows, depending on customer requirements >

- IPA certified ISO 14644-1 (e.g. HPF: EBK 41627)
- High vacuum (RGA) ISO 14644-15
- UL/CSA certification

Cabel approvals >

Low outgassing test at ChemTrace

Each application is analyzed by our engineers to better understand specific requirements. LEONI uses selected products for outstanding customization, when specific elements are required.

LEONI stands for high quality and high standards. This independent footprint enables the prevention of crosscontamination of forbidden materials in this industry and In addition to elective external certifications, such as ChemTrace ensures not only a climate-friendly environment for the producand Fraunhofer IPA, all LEONI clean room cables are manufaction of clean room application cables and cable systems but also tured and tested according to our strict clean room specifications. health-friendly production for our employees.

Product range

> Miniature cable

> Round cable

> Hybrid cable

> Coaxial cable

> Flat cable

> Cable assemblies & systems

Low emission Outgassing approved

Low particle emission raunhofer IPA approve



3

LEONI test center >

Long lifetime LEONI test center

For the Semiconductor and Display market, LEONI installed a clean room footprint of over 2000 m² with different cleanliness grades in accordance with ISO 14644-1 class 5–9.



For critical applications >

4

State State State State

Critical applications such as semiconductor production or production that takes place in ultra high vacuum needs low-outgassing insulation materials and special cleaning steps and processes.

The absence of silicone is guaranteed by consistent avoidance and sensitive control methods. In the final control step, the outgassing behavior of the assemblies is tested with a very sensitive mass spectrometer in an ultra-high vacuum chamber. Even the smallest outgassing impurities are detected.

LEONI develops and uses iacket and insulation materials that meet your demand

Special Sheathings for Special Applications

Clean cables from LEONI are equipped with special sheathing materials that are ideally suited for cleanliness-critical applications due to their high abrasion resistance and low particle emission.

08. 2021 www.leoni-machinery-sensors.com

your next project!

What does this mean >

You will benefit from LEONI's extensive knowledge and experi-

ence in cable and systems engineering. We will work hand-in-

• CAD 3D models ready to be integrated into your equipment

• 3D mapping of the cable assembly routing within your

• Component identification, selection and qualification

Engineered design with bill of materials and specifications

into one turnkey solution tailor-made for you.

Complete cable assembly consultation

Full project management services

design

product

Full Service for You – Custom Engineered

The intONE[™] team is dedicated to being your full service solution provider for


This means >

- You and your engineers can focus on developing the
- core technology of your application leave the rest to us.
- hand with your engineering team and combine our knowledge LEONI will be your partner throughout the entire lifecycle of your project to help you bring your concept to reality.

Tailor made complete intONE[™] product offering > Your cable assembly partner

- Rapid prototyping with less than four weeks turnaround times (based on available material and design complexity)
- Increased speed to market
- Intelligent cable technology and digitalization of your cable assembly
- 3D modelling of *molded* connectors, strain reliefs, grommets,
- Unique logistical service to assist in production volume sourcing
- Industry leading bulk cable minimum order of 300 ft /100 m





6

Wafer Handling Robots

Infrastructure Cabling



| 7

Round Cable

8

For fixed or flexible applications, LEONI's reliable and rugged products are adapted to your requirements.



The cables are manufactured, clean room packaged and assembled in an extremely clean factory under strict clean room conditions. All clean room cables are subjected to several cleaning steps and strict controls right up to shipment. Contamination with forbidden materials is eliminated during manufacturing.

Clean Room Round Cables for flexible use

- Optimized for comfortable installation
- Special low outgassing jacket material with improved mechanical strength
- Cables bundles up to 60 meters for easy cleanroom installation
- Lowest industry standard outgassing
- Optimized dimensions
- EMI robust

Vacuum Cables


- Emission-free materials
- Usable for low-particle production
- Exceptionally high degree of cleanliness in production
- Usable in ultra high vacuum environment
- Minimize of magnetic field disturbances

Infrastructure Cables

- Multi power cable : 0.5 240 mm²
- Multi signal cable
- Data cable Cat 5e Cat 7
- Lowest outgassing for Air Cleanliness Class 1 (tested at CHEMTRACE laboratory)
- Optimized cable diameters


Flat Cable

LEONI's High Performance Flex and Flexible Sleeve Technology replaces a traditional track system, with up to 1500 mm of supported free travel.



With a proven flex life greater than 10 million flex cycles and approved material for ISO Class 1 clean room. These cables are the reliable choice to decrease downtime.

- Tight bend radii from 25 to 150 mm (7.5 times the cable's height).
- Trackless solutions up to 1500 mm
- Proprietary clock spring design (reducing cable stress when rotating in the arm joint)
- Outer jacket made of low friction PTFE-tape
- High speed data and signal transmission
- Space saving design
- Engineering feedback resulting in design optimization of moved machine parts
- Tailor-made solutions including custom designed brackets and clamps for fixture in application




LEONI

9

High Performance Flex cables & cable solutions

Maximum reliability and flexible use up to 150 million cycles

& cable solutions



> Product specification – High Performance Flex technology

0000

Superior flexibilityUp to 150 million cycles at tight bending radii (7.5 times the cable height)Unlimited optionsLEONI can design any component that you requireSuperior performanceOptimized system performance with custom HPF cable assembliesLaminated designsCustom made for high end systems requiring higher accelerations and application speedsCustom componentsSpecial conductor materials, optimized layout and unique insulation materialsHybrid DesignsInclude custom coaxial signal wires, power and control wires, optical fibers, tubes and other componentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedJams/sCable width15–150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20°C-80°C/68°F – 176°F					
Superior performanceDetertering reny timp renewally berequiteSuperior performanceOptimized system performance with custom HPF cable assembliesLaminated designsCustom made for high end systems requiring higher accelerations and application speedsCustom componentsSpecial conductor materials, optimized layout and unique insulation materialsHybrid DesignsInclude custom coaxial signal wires, power and control wires, optical fibers, tubes and other componentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s ² Speed of travel>3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life0 °C – 80 °C / 68 °F – 176 °F	Superior flexibility	Up to 150 million cycles at tight bending radii (7.5 times the cable height)			
Laminated designsCustom made for high end systems requiring higher accelerations and application speedsCustom componentsSpecial conductor materials, optimized layout and unique insulation materialsHybrid DesignsInclude custom coaxial signal wires, power and control wires, optical fibers, tubes and other componentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel>3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Typical # of optimal filex life20 °C – 80 °C / 68 °F – 176 °F	Unlimited options	LEONI can design any component that you require			
Custom componentsSpecial conductor materials, optimized layout and unique insulation materialsHybrid DesignsInclude custom coaxial signal wires, power and control wires, optical fibers, tubes and other componentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel>3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Superior performance	Optimized system performance with custom HPF cable assemblies			
Hybrid DesignsInclude custom coaxial signal wires, power and control wires, optical fibers, tubes and other componentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel>3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Laminated designs	Custom made for high end systems requiring higher accelerations and application speeds			
Hybrid DesignscomponentsLow weightPermits high positioning speeds and accuracyComplete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel> 3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Custom components	Special conductor materials, optimized layout and unique insulation materials			
Complete cable assembliesIncluding mechanical and electrical componentsPrototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel> 3 m/sCable width15–150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20°C-80°C/ 68°F-176°F	Hybrid Designs				
Prototype orders300 ft / 100 m for new custom designsWeb spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel>3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Low weight	Permits high positioning speeds and accuracy			
Web spacingCan be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possibleTypical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel> 3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Complete cable assemblies	Including mechanical and electrical components			
Typical copper usedBare, silver plated copper in high strand counts as well as high strength copper alloysAccelerationUp to 45 m/s²Speed of travel> 3 m/sCable width15 – 150 mmTypical # of cables stackedUp to 5 cables in one clamp – depending on design more cables can be stackedClean room classIPA Air Cleanliness Class 1 (highest class possible)Temperature range for optimal flex life20 °C – 80 °C / 68 °F – 176 °F	Prototype orders	300 ft / 100 m for new custom designs			
Acceleration Up to 45 m/s ² Speed of travel > 3 m/s Cable width 15 - 150 mm Typical # of cables stacked Up to 5 cables in one clamp - depending on design more cables can be stacked Clean room class IPA Air Cleanliness Class 1 (highest class possible) Temperature range for optimal flex life 20 °C - 80 °C / 68 °F - 176 °F	Web spacing	Can be defined in order to optimize overall cable width – zero web up to 2.5 mm webs possible			
Speed of travel > 3 m/s Cable width 15 – 150 mm Typical # of cables stacked Up to 5 cables in one clamp – depending on design more cables can be stacked Clean room class IPA Air Cleanliness Class 1 (highest class possible) Temperature range for optimal flex life 20 °C – 80 °C / 68 °F – 176 °F	Typical copper used	Bare, silver plated copper in high strand counts as well as high strength copper alloys			
Cable width 15–150 mm Typical # of cables stacked Up to 5 cables in one clamp – depending on design more cables can be stacked Clean room class IPA Air Cleanliness Class 1 (highest class possible) Temperature range for optimal flex life 20 °C – 80 °C / 68 °F – 176 °F	Acceleration	Up to 45 m/s ²			
Typical # of cables stacked Up to 5 cables in one clamp – depending on design more cables can be stacked Clean room class IPA Air Cleanliness Class 1 (highest class possible) Temperature range for optimal flex life 20 °C – 80 °C / 68 °F – 176 °F	Speed of travel	> 3 m/s			
Clean room class IPA Air Cleanliness Class 1 (highest class possible) Temperature range for optimal flex life 20 °C - 80 °C / 68 °F - 176 °F	Cable width	15 – 150 mm			
Temperature range for optimal flex life 20 °C - 80 °C / 68 °F - 176 °F	Typical # of cables stacked	Up to 5 cables in one clamp – depending on design more cables can be stacked			
	Clean room class	IPA Air Cleanliness Class 1 (highest class possible)			
	Temperature range for optimal flex life	20 °C – 80 °C / 68 °F – 176 °F			
	Certifications	UL & CE			
Self supporting design option Up to 75 cm / 30 inches (depending on cable design)	Self supporting design option	Up to 75 cm / 30 inches (depending on cable design)			

88

> Product specification – Flexible Sleeve Technology

Superior flexibility	10 million cycles and b	
Typical bending radius	Typical bending radius	
Unlimited options	Set of readily available	
Web spacing	Standard web spacing	
Typical copper used	Bare and silver plated o	
Acceleration	Up to 30 m/s ²	
Speed of travel	Up to 3 m/s	
Cable width	22–127 mm	
Typical # of cables stacked	Ranging from 2–10	
Clean room class	IPA Air Cleanliness C	
Temperature range for optimal flex life	20 °C – 80 °C / 68 °F ·	
Certifications	UL & CE	
Self-supporting design option	Strength members t	

beyond

is approximately 75 mm if only standard components are used

e standard components

of 1 mm – 2 mm

copper, Class 5 stranding or better

Class 1 (highest class possible), ISO 14644-1

– 176 °F

that allow for 150 cm / 59 inches of supported free travel



LEONI Clean Room Product Range

We listen closely to our customers to ensure we deliver cables and systems meeting and exceeding their expectations. Bulk Cable, assemblies and ready solutions packed for usage in a clean room are typical clean room solutions.



CleanLine-Fix

Customized round cable for clean room infrastructure, built with approved clean room compounds and developed for low outgassing.

CleanLine-Flex

Customized round cable for power supply, data transmission and air/fluid handling. Special clean room compounds are optimized for low abrasion in high-speed applications.

High Performance Flex & Flexible Sleeve Technology

Customized PTFE flat cable (HPF) and modular system (FST) enable tight bend radii, maximum reliability and flexible use up to 150 million cycles.

High Performance Flex Vacuum

Customized PTFE flat cable for vacuum applications with unique low outgassing properties.

CleanLine-Vacuum

Customized round cable for ultra-high vacuum applications. The CleanLine-Vacuum cable fulfils all requirements for the lowest industry standard outgassing which is required for ISO 14644-15.

Applic	ations
	Die Attachment
Back End	IC Bonding Wire bonding, Thermoso Flip chip, Wafer Bonding Automated Tape Bondin
	IC Encapsulation Baking, Plating, Laserma Trimming and Forming



sonic bonding, ıg, ng arking, Cleaning Solvent Cleaning, Piranha Solution, RCA clean **Front End** Lithography lon Implantation Etching Deposition Planarization Wafer Testing Line Loader **Surface Mounted** ology Identification / Marking Screen Printing Coating Te In Circuit Test Line Unloader **Display Manufacturing Special Applications** Solar Panel Clean Room Infrastructure Wafer Lift

1 - Fir

CleanLine-Fix

1

Waferstage Sensors

Wafer Handling Robots

x	CL-Flex	HPF/FST	HPF-V	CL-V	
	X	High Performance Flex & Flexible Sleeve Technology	High Performance Flex Vacuum	CleanLine-Vacuum	
	e-Fle	form exibl echno	form	e-Va	
	CleanLine-Flex	High Performa Flex & Flexible Sleeve Technol	High Perform Flex Vacuum	nLin	
	Clea		Higl Flex	Clea	
	 ✓ 	 			
	V	v			
	~	~			
		~	~	<i>v</i>	
	~	 ✓ 	 	v	
	 ✓ 	 ✓ 	~	v	
	 ✓ 	マ マ マ	 ✓ 	v	
	 ✓ 	 ✓ 	 ✓ 	v	
	マ マ マ	マ マ マ	~	v	
	 ✓ 	 	~	V	
	 ✓ 	 ✓ 			
	 ✓ 	~			
	 	 			
	~	~			
	~	~			
	 ✓ 	✓			
	v	 ✓ 	 ✓ 	 ✓ 	
	~	 ✓ 			
	 	 			
	~	 ✓ 	✓	v	
	 ✓ 	 ✓ 	v	v	
	 ✓ 	✓	 ✓ 	V	

LEONI

Semiconductor Front End Production

Overview

14



LEONI offers cables and cable assemblies for test applications in clean rooms. Pioneers in semiconductor wafer inspection equipment already trust in our solutions. Our 20 kV high voltage cables with outer jacket made of low friction PTFE-tape have great performance during test procedures for Wafers. These systems test ments with LEONI clean room cables. the connections of the Wafer by high voltage impulses.

Electron-Beam Lithography

Silicon direct write, compound semiconductor and Mask making are manufacturing processes with high technical and cleanliness requirements. Our customer is the leader in designing and manufacturing of electron-beam lithography. They fulfill all these require-The customized design of LEONI Cables always are the specific solution which the customer needs.

Measuring Systems

LEONI's customer is a world market leader in multidimensional measuring technology and manufactures measuring systems for adjusting mirrors in lithographs. Therefore, LEONI delivers power, control and data cable assemblies. The clean room round cables are optimized for comfortable installation and are equiped with special low outgassing jacket materials with improved mechanical strength. LEONI engineers customized cable bundles are good for up to 60 meters making it easy for clean room installation.

Etching Equipment

Leading SMT machinery manufacturer and partner to the worlds leading semiconductor companies trust in LEONI clean room cables. Typical applications are front-end etching equipment. The laminated High Performance Flex Cables enable faster, more complex and precise etching equipment with a smaller foot-

LEONI's High Performance Flat Cables fulfil requirements in challenging environments such as highly sensitive and precise movements. These often occur in semiconductor and display frontend and backend installations and planar platforms. High Performance Flat Cables are the ideal solution for step-and-scanapplications, wafer process control, structuring of wafers and laser-based heat treatment of wafers. Some leading suppliers for high precision and high dynamic motion technology now use this and trust in LEONI solutions.



Cable for Wafer platform

Wafer Handling Robots

World leader in vacuum robotics, electric motor technology and leading manufacturers of wafer handling equipment use LEONI cables and cable assemblies for the full spectrum of wafer handling robotics. There are solutions for robotics for thin or bonded wafers and specialized wafer carriers. Robots for various uses around arc welding (including spot welding), handling, assembly, painting, transfer of liquid crystal panels, and transfer of semiconductor wafers are equipped with LEONI clean room cables. Especially the laminated High Performance Flex Cables perfectly fit for these kind of applications.



Semiconductor Back End production

Overview

16



LEONI offers cables and cable assemblies for bonding systems. Bonding is a key technology for manufacturing semiconductors. LEONI equips this machinery with highly flexible clean room cables. Best properties for speed, acceleration with lowest environment contaminations plus best EMV conditions LEONI combines magnetic tests. A leading supplier of with long flex life for less maintenance issues. Our customers are leading suppliers of semiconductor assembly equipment for the global semiconductor and electronics industries. we fulfil all requirements for flip chip bonding, wire bonding, die bonding, soft solder die bonding, multi module attach and laser bonding.

High Speed Camera

For high-speed cameras LEONI develops customized cables like a special GHz coax cable. This special GHz coax is an innovation to ensure important image transmission for position accuracy. The reliability was tested with more than 100 million flex cycles and had to pass harsh electrosemiconductor assembly and packaging equipment for the global semiconductor and electronics industries uses this cables for high speed cameras for tracking and inspection imaging.

For dispensing and pick and place production machines our drag less PTFE cable solution transport beside the important power and data as well bonding or molding substrate to the dies and PCBs. Our Air Cleanliness Class 1 approved solutions are perfect for the growing cleanliness standard of semiconductor and display production. Leading suppliers of high flexible SMT pick and place solutions with sophisticated dispenser systems trust in LEONI tailormade High Performance Flex Cables.

Pick & Place

Surface Mounting

0

0

/0-0 0

d

0

LEONI offers cables and cable assemblies for surface mounting machinery. These applications have special requirements for installed cables. LEONI perfectly meets the requirements regarding flexibility, lifetime and cleanliness.

The manufacturing processes of displays and wafers have very similar requirements to the semiconducter industry. This is the reason why LEONI clean room cables perfectly fulfil the needs for both of these industries. Leading providers of process innovation technologies of photovoltaics, electronics and lithium-ion battery technology know this and use especially LEONI High Performance Flex Cables. Optical inspection equipment for large flat panel displays, test cell and inspection equipment and production equipment e.g. laser glass cutting are just some examples in these market fields.



Further Clean Room Applications



Display Applications

Overview


Infrastructure Cabling

Infrastructure cabling of power, signal and data interconnection is an important topic for semiconductor manufacturer. LEONI offers clean room cables for infrastructure cabling which have lowest outgassing for Air Cleanliness Class 1. Multi power cable from diameters of 0.5 mm² up to 240 mm², multi signal cable and data cable Cat. 5e – Cat. 7 are provided.

LEONI

Close to Customers – Worldwide

Tailor-Made Products



Clean Room Cable locations > for Tailor-Made Products

CANADA LEONI Elocab Ltd. 258 McBrine Drive

Kitchener ON, N2R 1H8 Canada Phone +1 519-893-1155 infocables@leoni.com www.leoni-americas.com



You will find all current information on our sales network online >



Machinery & Sensors www.leoni-machinery-sensors.com machinery-sensors@leoni.com